

Specification text for durable marking of datum level and grid axes.

Item Description of works:

At least 1 marker to be fixed per room to permanently secure the datum level until building construction has been completed.

Datum markers by Messrs. Rothbucher Systems, Bayerisch Gmain,
Tel.: +49 (0)8651/2749 Fax: +49 (0)8651/3090,
incl. fitting (use self-adhesive backing and at least 1 mechanical fixing).

We recommend that the markers are sprayed with a colour spray at one corner.

For applications under plaster, use article no. **RS20** or **RS21** with plaster brush.

For applications on concrete and in door and window reveals, use article no. **RS10** or **RS11**.

When using datum markers fixed onto shuttering – to leave a negative imprint in the concrete – only use articles **RS10** or **RS11**!

Type: _____ Quantity: _____ pieces UP: _____ TOTAL: _____

In order to mark grid axes permanently through to completion of the building, fix 1 marker per axis at the outer walls and 1 marker each at all intermediate points, using datum markers or survey markers by Messrs. Rothbucher Systeme, Bayerisch Gmain, Tel.: +49 (0)8651/2749 Fax: +49 (0)8651/3090, using self-adhesive backing and at least 1 mechanical fixing.

For building sites without plaster works we recommend **RS70** survey markers in red or grey.

For building sites with plaster works, use **RS20** or **RS21** datum markers vertically and label with the axes symbol and number.

Type: _____ Quantity: _____ pieces UP: _____ TOTAL: _____