

ROTHBUCHER SYSTEME

Rothbucher Systeme, Lattenbergstr. 12, D-83457 Bayerisch Gmain

LATTENBERGSTRASSE 12
D-83457 BAYER. GMAIN

TEL. +49 (0) 86 51-27 49
FAX +49 (0) 86 51-30 90
MOBIL 0 171-73 14 961

e-mail: rs@meterriss.de
URL: www.meterriss.de

UID NR: DE 165 215 982

Technical data sheet

RSMK-FIX High quality adhesive


The values are average values. They serve merely for your information, but assume no warranty.

Basis	modified MS - Polymere
Consistency	thixotrop
Application temperature	+5 til +40 °C
Color	white
Curing through (24 hours)	3mm/24 h
Density	1569 kg/m ³
Skin forming time (23°C 55%RF)	10 til 15 min
Tensile strength (DIN 53504)	2,18 MPa
Temperature resistance (after curing)	-40°C to 100°C
Short time (2 til 3 hours)	+120 °C
Hardness Shore A DIN 53505	58
Modulus 100%	1,39 Mpa
Elongation at break: (DIN 53504)	335%
Shelf life (+5 til +25°C)	12 months

Deutschland
HypoVereinsbank
IBAN: DE79 7102 0072 0003 3493 30
SWIFT (BIC): HYVEDEMM410

Deutschland
Volksbank
IBAN: DE87 7109 0000 0001 0556 74
SWIFT (BIC): GENODEF1BGL

Österreich
P.S.K.
IBAN: AT68 6000 0000 8204 4534
SWIFT (BIC): OPSKATWW



ROTHBUCHER SYSTEME

Rothbucher Systeme, Lattenbergstr. 12, D-83457 Bayerisch Gmain

LATTENBERGSTRASSE 12
D-83457 BAYER. GMAIN

TEL. +49 (0) 86 51-27 49
FAX +49 (0) 86 51-30 90
MOBIL 0 171-73 14 961

e-mail: rs@meterriss.de
URL: www.meterriss.de

UID NR: DE 165 215 982

Properties:

- adhesion in next to no time
- bonds immediately
- is the new generation of the mounting adhesive.
- hardens quickly by
- is very well suited for natural stones
- is not shrinking
- is free from isocyanate, phthalate, solvent and silicone
- odourless
- replaces conventional supports such as screws, bolts, rivets or welding.
- resistant to UV radiation, water, chlorine, etc.
- bonding of various materials
- Isocyanat and silicone free
- suitable for varnishing and coating
- permanently elastic and universally applicable
- fast, simple and cost-effective bonding of materials

RSMK-FIX is the new generation of mounting adhesives and has very strong initial bonding. Bonding of heavy parts in vertical positions and ceiling mounting. Unlike with conventional adhesives, it is also possible to bond heavy items such as stones, wood, tiles and metals to walls and ceilings with RSMK-FIX without sagging and sliding off.

Areas of application:

Universal adhesive for bonding various building materials such as: (natural) stone, concrete, mirrors, glass, plasterboard, polycarbonate, PS, PU, PVC, polyester, plastics, email, ceramic, copper, lead, zinc, aluminium, metals, R.V.S., wood etc. RSMK-FIX is free of isocyanates, phtalat, solvents and silicone. Extreme high initial grab to bond heavy building materials without the use of Clamps and/or tape. RSMK-FIX for inside and outside use in building and industry constructions

Instructions:

The parts to be bonded must be clean, oil- and grease free
Apply RSMK-FIX on one side, part position and firmly press down.
The liability is immediate.

RoHS compliant

Packaging:

12 cartridges á 450 g

Deutschland
HypoVereinsbank
IBAN: DE79 7102 0072 0003 3493 30
SWIFT (BIC): HYVEDEMM410

Deutschland
Volksbank
IBAN: DE87 7109 0000 0001 0556 74
SWIFT (BIC): GENODEF1BGL

Österreich
P.S.K.
IBAN: AT68 6000 0000 8204 4534
SWIFT (BIC): OPSKATWW